Docket No. AUS920030412US1

METHOD AND APPARATUS FOR MANAGING A REMOTE DATA PROCESSING SYSTEM

BACKGROUND OF THE INVENTION

5

1. Technical Field:

The present invention relates generally to an improved data processing system and in particular, a method and apparatus for processing data. Still more

10 particularly, the present invention provides a method, apparatus, and computer instructions for managing a remote host data processing system.

2. Description of Related Art:

15 In network data processing systems, remote wake-up abilities are often provided for clients. This type of feature allows a client that is in a sleep mode to be woken up through the network. With this feature, a system administrator or other user may wake-up a sleeping

20 client by sending a selected type of network packet. This packet is called a "wake-up packet". For example, with a network adapter, such as an Ethernet controller, the adapter is modified to listen for a special wake-up packet on a local area network (LAN) address even when

25 the computer in which the network adapter is located is asleep in a power conservation mode. Upon receiving this packet, the network adapter checks the packet content to ensure that the packet is destined for this particular client. If the packet is destined for the client, the

30 adapter wakes up the sleeping client. This type of

technology also is referred to as "magic packet technology".

This type of feature may be used on a large network data processing system in which the system administrator's data processing system is located on a different subnet from the clients that are being managed. A subnet is a division of a network into an interconnected, but independent, segment, or domain, in order to improve performance and security. In generating a wake-up packet, the remote data processing system's 48-bit media access control (MAC) address is encoded into the wake-up packet. A MAC address is a unique serial number that is used to identify a network card. Thereafter, the wake-up packet is broadcast to address 255.255.255.255 if the remote data processing system is on the same subset. Otherwise, this packet is sent to a subnet-directed broadcast address if the remote data processing system is located on another subnet.

To wake up a remote data processing system on a subnet, the administrator needs to have the remote data processing system's MAC address and subnet mask in addition to having the name of the remote data processing system or the IP address for the remote data processing system. The technique is used by the IP protocol to filter messages into a particular network segment (subnet). The subnet mask is a binary pattern that is stored in the client data processing system, server or router and is matched up with the incoming Internet Protocol (IP) address to determine whether to accept or reject the packet. It is inconvenient for an

Docket No. AUS920030412US1

administrator to obtain a MAC address and subnet mask for all remote data processing systems managed by an administrator, especially when large numbers of clients are managed.

5   Therefore, it would be advantageous to have an improved method, apparatus, and computer instructions for identifying host information such as a MAC address and a subnet mask, for a remote data processing system.

Docket No. AUS920030412US1

SUMMARY OF THE INVENTION

The present invention provides a method, apparatus, and computer instructions for providing host information. A request is received for host information for a remote computer from a requestor wherein the request includes one of a host name or an Internet Protocol address. The host information is received from a requestor. A media access control address and a subnet mask is identified using the request, and a response is returned to the requestor, wherein the response includes the media access control address and the subnet mask.

Docket No. AUS920030412US1

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the
5   invention are set forth in the appended claims. The
invention itself, however, as well as a preferred mode of
use, further objectives and advantages thereof, will best
be understood by reference to the following detailed
description of an illustrative embodiment when read in
10   conjunction with the accompanying drawings, wherein:

Figure 1 is a pictorial representation of a network
of data processing systems in which the present invention
may be implemented;

Figure 2 is a block diagram of a data processing
15   system that may be implemented as a server in accordance
with a preferred embodiment of the present invention;

Figure 3 is a block diagram illustrating a data
processing system in which the present invention may be
implemented;

20   **Figure 4** is a diagram illustrating components used
in obtaining and providing host information for managing
remote hosts in accordance with a preferred embodiment of
the present invention;

Figure 5 is a diagram illustrating a text record in
25   accordance with a preferred embodiment of the present
invention;

Figure 6 is a flowchart of a process for obtaining
host information from a DHCP client in accordance with a
preferred embodiment of the present invention;

Docket No. AUS920030412US1

Figur 7 is a flowchart of a process for a client to obtain an IP address from a DHCP server in accordance with a preferred embodiment of the present invention;

Figure 8 is a flowchart of a process for updating

5   host information in a name-to-address mapping file in accordance with a preferred embodiment of the present invention;

Figure 9 is a flowchart of a process for allowing a DNS server to be dynamically updated with host

10 information in accordance with a preferred embodiment of the present invention; and

Figure 10 is a flowchart of a process for waking up a remote host in accordance with a preferred embodiment of the present invention.

Docket No. AUS920030412US1

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, **Figure 1** depicts a
5   pictorial representation of a network of data processing
systems in which the present invention may be implemented.
Network data processing system **100** is a network of
computers in which the present invention may be
implemented. Network data processing system **100** contains
10   a network **102**, which is the medium used to provide
communications links between various devices and computers
connected together within network data processing system
100. Network **102** may include connections, such as wire,
wireless communication links, or fiber optic cables.
15   In the depicted example, server **104** is connected to
network **102** along with storage unit **106**. In addition,
clients **108**, **110**, and **112** are connected to network **102**.
These clients **108**, **110**, and **112** may be, for example,
personal computers or network computers. In the depicted
20   example, server **104** provides data, such as boot files,
operating system images, and applications to clients **108-
112**. Clients **108**, **110**, and **112** are clients to server **104**.
Network data processing system **100** may include additional
servers, clients, and other devices not shown. In the
25   depicted example, network data processing system **100** is
the Internet with network **102** representing a worldwide
collection of networks and gateways that use the
Transmission Control Protocol/Internet Protocol (TCP/IP)
suite of protocols to communicate with one another. At
30   the heart of the Internet is a backbone of high-speed data

Docket No. AUS920030412US1

communication lines between major nodes or host computers,
consisting of thousands of commercial, government,
educational and other computer systems that route data and
messages. Of course, network data processing system **100**

5   also may be implemented as a number of different types of
networks, such as for example, an intranet, a local area
network (LAN), or a wide area network (WAN). **Figure 1** is
intended as an example, and not as an architectural
limitation for the present invention.

10   Referring to **Figure 2**, a block diagram of a data
processing system that may be implemented as a server,
such as server **104** in **Figure 1**, is depicted in accordance
with a preferred embodiment of the present invention.
Data processing system **200** may be a symmetric

15   multiprocessor (SMP) system including a plurality of
processors **202** and **204** connected to system bus **206**.
Alternatively, a single processor system may be employed.
Also connected to system bus **206** is memory
controller/cache **208**, which provides an interface to local

20   memory **209**. I/O bus bridge **210** is connected to system bus
206 and provides an interface to I/O bus **212**. Memory
controller/cache **208** and I/O bus bridge **210** may be
integrated as depicted.

Peripheral component interconnect (PCI) bus bridge

25   **214** connected to I/O bus **212** provides an interface to PCI
local bus **216**. A number of modems may be connected to PCI
local bus **216**. Typical PCI bus implementations will
support four PCI expansion slots or add-in connectors.
Communications links to clients **108-112** in **Figure 1** may be

Docket No. AUS920030412US1

provided through modem **218** and network adapter **220**
connected to PCI local bus **216** through add-in boards.

Additional PCI bus bridges **222** and **224** provide
interfaces for additional PCI local buses **226** and **228**,
5   from which additional modems or network.adapters may be
supported.   In this manner, data processing system **200**
allows connections to multiple network computers.   A
memory-mapped graphics adapter **230** and hard disk **232** may
also be connected to I/O bus **212** as depicted, either
10   directly or indirectly.

Those of ordinary skill in the art will appreciate
that the hardware depicted in **Figure 2** may vary.   For
example, other peripheral devices, such as optical disk
drives and the like, also may be used in addition to or in
15   place of the hardware depicted.   The depicted example is
not meant to imply architectural limitations with respect
to the present invention.

The data processing system depicted in **Figure 2** may
be, for example, an IBM eServer pSeries system, a product
20   of International Business Machines Corporation in Armonk,
New York, running the Advanced Interactive Executive
(AIX) operating system or LINUX operating system.

With reference now to **Figure 3**, a block diagram
illustrating a data processing system is depicted in which
25   the present invention may be implemented.   Data processing
system **300** is an example of a client computer.   Data
processing system **300** employs a peripheral component
interconnect (PCI) local bus architecture.   Although the
depicted example employs a PCI bus, other bus
30   architectures such as Accelerated Graphics Port (AGP) and

Docket No. AUS920030412US1

Industry Standard Architecture (ISA) may be used.
Processor **302** and main memory **304** are connected to PCI
local bus **306** through PCI bridge **308**. PCI bridge **308** also
may include an integrated memory controller and cache

5   memory for processor **302**. Additional connections to PCI
local bus **306** may be made through direct component
interconnection or through add-in boards. In the depicted
example, local area network (LAN) adapter **310**, SCSI host
bus adapter **312**, and expansion bus interface **314** are

10   connected to PCI local bus **306** by direct component
connection. In contrast, audio adapter **316**, graphics
adapter **318**, and audio/video adapter **319** are connected to
PCI local bus **306** by add-in boards inserted into expansion
slots. Expansion bus interface **314** provides a connection

15   for a keyboard and mouse adapter **320**, modem **322**, and
additional memory **324**. Small computer system interface
(SCSI) host bus adapter **312** provides a connection for hard
disk drive **326**, tape drive **328**, and CD-ROM drive **330**.
Typical PCI local bus implementations will support three

20   or four PCI expansion slots or add-in connectors.

An operating system runs on processor **302** and is used
to coordinate and provide control of various components
within data processing system **300** in **Figure 3**. The
operating system may be a commercially available operating

25   system, such as Windows XP, which is available from
Microsoft Corporation. An object oriented programming
system such as Java may run in conjunction with the
operating system and provide calls to the operating system
from Java programs or applications executing on data

30   processing system **300**. "Java" is a trademark of Sun

Docket No. AUS920030412US1

Microsystems, Inc. Instructions for the operating system, the object-oriented operating system, and applications or programs are located on storage devices, such as hard disk drive **326**, and may be loaded into main memory **304** for

5   execution by processor **302**.

Those of ordinary skill in the art will appreciate that the hardware in **Figure 3** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash read-only memory (ROM), equivalent

10   nonvolatile memory, or optical disk drives and the like, may be used in addition to or in place of the hardware depicted in **Figure 3**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

15   As another example, data processing system **300** may be a stand-alone system configured to be bootable without relying on some type of network communication interfaces. As a further example, data processing system **300** may be a personal digital assistant (PDA) device, which is

20   configured with ROM and/or flash ROM in order to provide non-volatile memory for storing operating system files and/or user-generated data.

The depicted example in **Figure 3** and above-described examples are not meant to imply architectural

25   limitations. For example, data processing system **300** also may be a notebook computer or hand held computer in addition to taking the form of a PDA. Data processing system **300** also may be a kiosk or a Web appliance.

The present invention provides a method, apparatus,

30   and computer instructions for identifying host

Docket No. AUS920030412US1

information for a remote data processing system. In
particular, the mechanism of the present invention
identifies a MAC address and subnet mask for a remote
data processing system that is to be woken up.

5   According a preferred embodiment of the present
invention, if the remote data processing system, also
referred to as a remote host, uses dynamic host
configuration protocol (DHCP) to obtain an IP address,
the DHCP server obtains the MAC address and subnet mask

10   of the remote host as part of the process of assigning an
IP address to this client. The mechanism of the present
invention sends this information, along with the IP
address, to a domain name system (DNS) server. If the
remote host has a static IP address, this information is

15   sent to the DNS server at the time the static address is
provisioned for the remote host. As a result, when a
remote host is to be woken up, an administrator, at a
managing data processing system or host, sends a DNS
query to a DNS server to obtain the MAC address and

20   subnet mask. In this manner, an administrator or managing
host is not required to know all of the host information
for managed remote hosts. Such a feature is especially
useful with respect to data processing systems in which
IP addresses may change based on using DHCP.

25   Turning next to **Figure 4**, a diagram illustrating
components used in obtaining and providing host
information for managing remote hosts is depicted in
accordance with a preferred embodiment of the present
invention. As illustrated, administration computer **400** -

30   is a managing host that generates wake-up packet **402** to

wake-up target computer **404**. Target computer **404** is a remote host in this example. In generating wake-up packet **402**, administration computer **400** needs an IP address or name for target computer **404**. With the IP

5 address, the host name for target computer **404** may be obtained from DSN server **408**. If the host name is known, the IP address may be obtained from DNS server **408**.

Administration computer **400** also needs a MAC address and a subnet mask for target computer **404**. The MAC

10 address and subnet mask are the host information that is needed to generate wake-up packet **402**. In these examples, this information may be obtained from DNS sever **408**. DNS server **408** contains a mapping of names-to-addresses and a mapping of addresses-to-names in database

15 **410**. The mapping information in this database is loaded into DNS server cache **411**.

To obtain the host information, administration computer **400** sends "TXT" DNS query **406** to DNS server **408**. This query includes the host name for target computer

20 **404**. In these examples, this host information is located in the name-to-address mapping file. In response to receiving "TXT" DNS query **406**, DNS server **408** queries DNS server cache **411** for host information, such as the MAC address and subnet mask. In this example, "TXT" DNS

25 query **406** is for a text record for target computer **404**.

The host name is used to identify this record in DNS server cache **411** to obtain the MAC address and the subnet mask for use in generating a wake-up packet. When the text record is found, this record is returned to

30 administration computer **400** as response **412**. With this

14

information, administration computer **400** places the appropriate host information into wake-up packet **402**.

The text records containing host information in database **410** may be provisioned on DNS server **408** through
5   different mechanisms. One mechanism involves having DHCP server **414** obtain the host information from target computer **404** when assigning IP addresses. This mechanism is used with dynamic IP addresses. In the case of static IP addresses, the host information may be provisioned
10   directly by a user or administrator.

In this example, with dynamic IP address, target computer **404** uses DHCP to obtain an IP address from DHCP server **414**. As part of this process, DHCP server **414** retrieves host information **416** from target computer **404**.
15   As illustrated, host information **416** is the MAC address and subnet mask for target computer **404**. DHCP server **414** sends host information **416** as an update to DNS server **408**. This information is placed into DNS server cache **411**. Thus, queries from users, such as one at
20   administration computer **400**, may be processed to provide host information needed for management activities, such as waking up a remote host with a wake-up packet.

DNS server cache **411** contains the most up-to-date host information in these examples. Periodically, DNS
25   server **408** updates database **410** with information from DNS server cache **411**. In particular, a name-to-address mapping file and an address-to-name mapping file in database **410** is updated from DNS server cache **411**.

In the case in which target computer **404** has a
30   static IP address, the MAC address and subnet mask is

Docket No. AUS920030412US1

provided to DNS sever **408** by a user or system
administrator. This provisioning of host information is
typically performed when the static IP address is
provisioned. This information only needs to be provided

5   to DNS server **408** once. As a result, future queries for
host information causes DNS server **408** to provide that
information to the requestors. In this manner, an
administrator does not need to know all of the host
information for a remote host. Knowledge of the IP

10   address or name of the remote host is sufficient.

Turning next to **Figure 5**, a diagram illustrating a
text record is depicted in accordance with a preferred
embodiment of the present invention. Text record **500** is
an example of a record that may be located in a DNS

15   server database, such as database **410** in **Figure 4**. Text
record **500** includes MAC address **502** and subnet mask **504**.
In these examples, the data populating these fields are
strings. MAC address field **502** and subnet mask **504** also
include a key word as a prefix to the string. For

20   example, the string "MAC" is a prefix to the following
for MAC address field **502**: "MAC:00:04:ac:17:06:87".
Subnet mask **504** contains "Subnetmask" as a prefix for:
"Subnetmask:0xffffff00". This information is included
for text records for name-to-address files in a DNS

25   database.

Turning next to **Figure 6**, a flowchart for obtaining
host information from a DHCP client depicted in
accordance with a preferred embodiment of the present
invention. The process illustrated in **Figure 6** may be

implemented in a DHCP server, such as DHCP server **414** in
Figure 4.

   The process begins by receiving a discover message
for an IP address from a client with the client's MAC
5 address (step **600**). An offer is sent to the client with
the IP address and other options (step **602**). Other
options may include, for example, gateways, DNS servers
and subnet masks. A broadcast request is then received
from the client indicating that the client accepts the
10 offer (step **604**). Thereafter, an acknowledgement is sent
to the client in response to the client receiving the
broadcast request. Afterward, an update is sent to DNS
server (step **608**) with the process terminating
thereafter. This update includes the MAC address, the IP
15 address, and the subnet mask.

   Turning next to **Figure 7**, a flowchart of a process
for a client to obtain an IP address from a DHCP server
is depicted in accordance with a preferred embodiment of
the present invention. The process illustrated in **Figure
20 7** may be implemented in a data processing system, such as
target computer **404** in **Figure 4**.

   The process begins by sending a discover message for
an IP address to a DHCP server (step **700**). This discover
message includes the MAC address of the host. An offer
25 is received from a DHCP server with the IP address and
other options (step **702**). In response to receiving this
offer, a request is broadcast to the DHCP server
accepting the offer (step **704**) with the process
terminating thereafter.

Docket No. AUS920030412US1

Turning now to **Figur** 8, a flowchart of a process for updating host information in a name-to-address mapping file is depicted in accordance with a preferred embodiment of the present invention. This process allows
5   for updates to be made when a static IP address is assigned.

The process begins by stopping the DNS server (step **800**). A MAC address and subnet mask is added as part of the text record of that client in the name-to-address
10   mapping file (step **802**). Then, the DNS server is restarted (step **804**). The DNS server then loads the address to name mapping file and the name to address mapping file in to the cache (step **806**) with the process terminating thereafter.
15   Turning now to **Figure 9**, a flowchart of a process for allowing a DNS server to be dynamically updated with host information is depicted in accordance with a preferred embodiment of the present invention. The process is illustrated in **Figure 9** may be used with a DNS
20   server, such as DNS server **408** in **Figure 4**.

The process begins by configuring the DNS server to allow dynamic updates from a specific host or from any host to configure the DNS server to write information to a cache in which the information is used to update a
25   name-to-address mapping file after a fixed period of time (step **900**).

Next, the DNS server is started (step **902**). An "nsupdate" tool is used to dynamically update the MAC address and the subnet address as part of the text record
30   in the DNS server's cache (step **904**). The "nsupdate" tool

may be obtained from the Internet Software Consortium.
This tool is one that may be used by a user to
dynamically update DNS mapping information in the DNS
server cache. After the fixed period of time passes, the
5   mapping information in the cache is used to update the
name-to-address mapping file (step **906**) with the process
terminating thereafter.

Turning now to **Figure 10**, a flowchart of a process
for waking up a remote host is depicted in accordance
10   with a preferred embodiment of the present invention.
The process illustrated in **Figure 10** may be implemented
in a computer, such as administration computer **400** in
Figure 4. This process may be initiated with a user
providing only a remote host name.

15   The process begins by sending a type "A" DNS query
to a DNS server for host information (step **1000**). This
query includes the host name, but requires no other host
information. This type of query results in an IP address
being returned for the host name. After the query has
20   been sent, an IP address is received (step **1002**). Next,
a type "TXT" DNS query is sent to the DNS server (step
1004). This query also requires only a host name and is
used to obtain a text record. Thereafter, a text record
is received from the DNS server.

25   The MAC address and subnet mask is extracted from
the text record returned from the DNS server (step **1008**).
This information is used to calculate a subnet broadcast
address (step **1010**). The MAC address received in the
text record from the DNS server is encoded into a wake-up
30   packet (step **1012**). The wake-up packet is then sent to

Docket No. AUS920030412US1

the subnet-directed broadcast address (step **1014**) with the process terminating thereafter.

A similar process may be used to send a wake-up packet to a remote host in which only an IP address is
5   used. In this case, the first query sent is a type "PTR" DNS query containing the IP address, which results in a host name being returned for the IP address. Steps similar to steps **1004-1014** are used as described above. In step **1004**, the type "TXT" DNS query is sent using the
10   host name. In these examples, the host information is present in the name-to-address mapping file.

Thus, the present invention provides a method, apparatus, and computer instructions for obtaining host information for a remote host or data processing system.
15   The mechanism of the present invention avoids a user or process having to store or identify all of the host information for a remote host. The host information needed may be obtained from a server, such as a DNS server, using a query containing a host name for the
20   remote host. Host information, such as a MAC address and a subnet mask is supplied in response to the query. This information may then be used to direct packets, such as wake-up packets, to a remote host to wake up the remote host. Management of the remote data processing system is
25   made more convenient for a user or administrator when the user or administrator only needs to provide a host name or IP address to generate a wake-up packet.

It is important to note that while the present invention has been described in the context of a fully
30   functioning data processing system, those of ordinary

skill in the art will appreciate that the processes of
the present invention are capable of being distributed in
the form of a computer readable medium of instructions
and a variety of forms and that the present invention

5   applies equally regardless of the particular type of
signal bearing media actually used to carry out the
distribution. Examples of computer readable media
include recordable-type media, such as a floppy disk, a
hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and

10   transmission-type media, such as digital and analog
communications links, wired or wireless communications
links using transmission forms, such as, for example,
radio frequency and light wave transmissions. The
computer readable media may take the form of coded

15   formats that are decoded for actual use in a particular
data processing system.

The description of the present invention has been
presented for purposes of illustration and description,
and is not intended to be exhaustive or limited to the

20   invention in the form disclosed. Many modifications and
variations will be apparent to those of ordinary skill in
the art. The embodiment was chosen and described in
order to best explain the principles of the invention,
the practical application, and to enable others of

25   ordinary skill in the art to understand the invention for
various embodiments with various modifications as are
suited to the particular use contemplated.